



PRODUCT FEATURES

- **TUNABLE POWER & COLOR**
- Photocell included (ON/OFF switch)
- ADC12 Aluminum Heat Sink Housing
- Outdoor Powder Coating
- Bronze Finish
- IP65 Rating - Suitable for Wet Locations
- Dimming: 0-10V/PWM/VR
- 50,000 Hour Lifetime Rating
- High Light Transmittance PC, Anti-UV and Fire Resistance Lens
- Highly Conductive, Waterproof, Aging Resistance, Salt Mist Resistance Aluminum LED Board
- DLC Premium Listed
- UL Certified
- Operating Temperature: -40°F to 104°F (-40°C to 40°C)
- 5-Year Limited Warranty

PRODUCT SPECIFICATIONS

MODEL	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN)	EFFICIENCY (lm/W)	MOUNT	VOLTAGE (V)
CLF4-60VCCTKNBR-TN	40	5,200	3000	9.6 x 9.25 x 2.2	130	KNUCKLE	120 - 277
	50	6,500	4000				
	60	7,800	5000				
CLF4-60VCCTYKBR-TN	40	5,200	3000	10.2 x 8.6 x 2.25	130	YOKE	120 - 277
	50	6,500	4000				
	60	7,800	5000				

