



LED SQUARE CANOPY




PRODUCT FEATURES

- Die-Cast Aluminum Alloy Housing
- Bronze Finish
- IP65 Rating - Suitable for Wet Locations
- 100-277 Voltage Rating, PF > 0.9, THD < 20%
- CRI > 80
- Dimmable
- Striped Clear Plastic Lens
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- UL / cUL Certified
- Operating Temperature: -22°F to 113°F (-30°C to 45°C)

PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN) (L x W x H)	EFFICIENCY (Lm/W)	BEAM ANGLE
CLCN11-75W-SAA-50K	L75W5KCNSCL11	75	9,400	5000	10.04 x 10.04 x 4.93	125	160°

PHOTOMETRY



Flux out: 7721 lm

3.281ft 1m	37.27, 137.4fc 401.2, 1479lx	15.64ft 476.82cm
6.562ft 2m	9.317, 34.34fc 100.3, 369.6lx	31.29ft 953.64cm
9.843ft 3m	4.141, 15.26fc 44.57, 164.3lx	46.93ft 1430.46cm
13.12ft 4m	2.329, 8.585fc 25.07, 92.41lx	62.57ft 1907.28cm
16.4ft 5m	1.491, 5.495fc 16.05, 59.14lx	78.22ft 2384.10cm
Height	Havg, Hmax	Angle: 134.49deg Diameter

DIAGRAM

