



# LED SQUARE CANOPY




## PRODUCT FEATURES

- Die-Cast Aluminum Alloy Housing
- Bronze Finish
- IP65 Rating - Suitable for Wet Locations
- 100-277 Voltage Rating, PF > 0.9, THD < 20%
- CRI > 80
- Dimmable
- Striped Clear Plastic Lens
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- UL / cUL Certified
- Operating Temperature: -22°F to 113°F (-30°C to 45°C)

## PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN) (L x W x H)	EFFICIENCY (Lm/W)	BEAM ANGLE
CLCN11-40W-SAA-50K	L40W5KCNSCL11	40	5,000	5000	8.94 x 8.94 x 4.53	125	160°

## PHOTOMETRY



Height	Havg, Emax	Angle: 124.15deg	Diameter
3.281ft	28.97, 74.49fc		12.38ft
1m	311.8, 801.8lx		377.33cm
6.562ft	7.242, 18.62fc		24.76ft
2m	77.96, 200.4lx		754.65cm
9.843ft	3.219, 8.276fc		37.14ft
3m	34.65, 89.09lx		1131.98cm
13.12ft	1.811, 4.655fc		49.52ft
4m	19.49, 50.11lx		1509.31cm
16.4ft	1.159, 2.979fc		61.9ft
5m	12.47, 32.07lx		1886.64cm

## DIAGRAM

