



# LED ROUND CANOPY



## PRODUCT FEATURES


- Die-Cast Aluminum Alloy Housing
- Bronze Finish
- IP65 Rating - Suitable for Wet Locations
- 100-277 Voltage Rating, PF > 0.9, THD < 20%
- CRI > 80
- Dimmable
- Striped Clear Plastic Lens
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- UL / cUL Certified
- Operating Temperature: -22°F to 122°F (-30°C to 50°C)

## PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	DIMENSIONS (IN) D x H	EFFICIENCY (Lm/W)	BEAM ANGLE
CLCN11-75W-RAA-BR50	L75W5KCNRL11	75	9,400	5000	Ø 11.02 x 3.11	125	150°

## PHOTOMETRY

## DIAGRAM



Dist(m)	Enadir(lx)	Dh/Dv_B(m)	S_B(sq.m)	Eav_B(lx)
1.0	1512.92	6.92/6.73	38.3	98.31
2.0	378.23	13.83/13.46	153.0	24.58
3.0	168.10	20.75/20.20	344.3	10.92
4.0	94.56	27.66/26.93	612.2	6.14
5.0	60.52	34.58/33.66	956.5	3.93
6.0	42.03	41.49/40.39	1377.4	2.73
7.0	30.88	48.41/47.13	1874.8	2.01
8.0	23.64	55.32/53.86	2448.7	1.54
9.0	18.68	62.24/60.59	3099.1	1.21
10.0	15.13	69.15/67.32	3826.0	0.98

Dh Beam Angle(B): H147.7 V146.9 Field Angle(F): H171.8 V171.7

