




# LED DUAL MODE TUBES



## PRODUCT FEATURES

- Direct Replacement / Plug & Play Mode (Type A) \*
- Retrofit / Bypass Mode - Double Ended (Type B)
- Film Coated Shatter Resistant Glass Tube
- Frosted
- 0-10V Dimming Available
- 120-277 Voltage Rating, PF > 0.9
- CRI = 83
- G13 Mounting
- NSF Certified
- UL Certified
- DLC Listed
- 50,000 Hour Lifetime Rating
- 5-Year Limited Warranty
- Operating Temperature Range: -4°F to 113°F (-20°C to 45°C)

\* See Ballast Compatibility Chart

## PRODUCT SPECIFICATIONS

MODEL	ITEM #	POWER (W)	LUMENS (LM)	CCT (K)	LENGTH (IN)	EFFICIENCY (Lm/W)	BEAM ANGLE	FIELD ANGLE
CLT97-15WAB3D (40K)	L15T84KABCL97	15	1950	4000	47.76	130	200°	340°
CLT97-15WAB3D (50K)	L15T85KABCL97	15	1950	5000	47.76	130	200°	340°
CLT97-18WAB3D (35K)	L18T835KABCL97	18	2200	3500	47.76	122	200°	340°
CLT97-18WAB3D (40K)	L18T84KABCL97	18	2200	4000	47.76	122	200°	340°
CLT97-18WAB3D (50K)	L18T85KABCL97	18	2200	5000	47.76	122	200°	340°

