

MODEL:	TYPE
PROJECT:	
PREPARED BY:	
DATE:	

PID: SL960T8BC

SPECIFICATIONS:

FEATURES

- Integrated extruded aluminum heat sink
- Aluminum + PC casing
- Plastic Frosted lens
- Compatible with majority of T8 electronic ballast
- May bypass ballast for direct wire
- Single or Double-ended connection
- Suitable for enclosed fixtures

ENERGY DATA

- Internal driver 100-277V
- Operation Temperature -4 ~122 F
- Power Factor > 0.95
- G13 (Medium Bi-Pin)
- Non-dimming

ORDERING GUIDE

SKU	Description	Wattage	Lumens	Color Temp	DLC
11052437-1	SL960T8BC-48-14W-100/277V-4000-F-120-I-N-G13-SD-1 DLC PXXHORE9	14W	2145	4000K	YES
11052439-1	SL960T8BC-48-14W-100/277V-5000-F-120-I-N-G13-SD-1 DLC PDJF097H	14W	2175	5000K	YES
11052451-1	SL960T8BC-48-18W-100/277V-4000-F-120-I-N-G13-SD-1 DLC PDF53ZKF	18W	2700	4000K	YES
11052453-1	SL960T8BC-48-18W-100/277V-5000-F-120-I-N-G13-SD-1 DLC PRYNMCN7	18W	2700	5000K	YES



WARRANTY

- 5-year warranty
- *We recommend testing a trial lamp before placing a large order*

