

# STRAITS LED CRANE LIGHT

PID: SL930SAF - 24W





#### **APPLICATIONS:**

- SIGNALS DANGER ZONES
- HAZARDOUS WORK AREAS
- CONSTRUCTION SITES

#### **SPECIFICATIONS:**

#### **FEATURES**

Reduce accidents in hazardous areas

Suitable for Indoor and outdoor use

Built in cooling convection design

Min starting temperature -40°F (-40°C)

Max starting temperature 185°F (85°C)

#### **ENERGY DATA**

Driver: 10-110V

Power Factor > 1.00

Surge protection

#### **LED MODULES**

CREE LED chips

50,000 hour rated life hours

Available Kelvin temperature of 60K

Beam angle: 5°

(adjustable 150° with yoke bracket)

Red caution light

#### **ADD ONS**

150W Driver - 24V

Extension cord

### MOUNTING

Yoke mounting

### **CERTIFICATIONS**

IP67 Rated

UL certified

### WARRANTY


2 year warranty

### **PRODUCT DETAILS**

Product	Input (VAC)	Lumens	Efficacy	CCT <sup>1</sup>	Beam Angle	Rated Life (hours)
RED - 24W	10-110V	2,000	20.79	60K	5°-150°	50,000

### **PRODUCT DIMENSIONS**

Length	Width	Height
(Inches)	(Inches)	(Inches)
7.09"	1.93"	1.97"




### **INSTALLATION HEIGHT AND BEAM LENGTH**

Installed Height	5 ft	10 ft	15 ft	The length of the beam is about twice the size of the installed height.
Horizontal Beam Length	10 ft	20 ft	30 ft	

## **LED IN ACTION**

Increase safety and reduce accidents using the Straits Crane Light. It's bright warning light gives pedestrians a clear visual warning. It is much more effective than sound alarm systems.







### **ORDERING GUIDES**

ORDER CODE	WATTS	VOLTS	COLOR
SL930SAF	24W	SU	Red

ORDER EXAMPLE: SL930SAF - 24W - SU - RED

ORDER CODE	WATTS	VOLTS
SLDR (Driver)	150W	24V

ORDER EXAMPLE: SLDR - SU - 150W - 24V